



Technical Data

Specification & Capacities

JF545.2




EN 12999:2020

29.08.2024 | Rev0.0

[m] [kg]


OVERALL DIMENSIONS

(with jib and low marking pads)



H	WITH V20 winch	2830
	WITH V30 winch	2900

STABILITY AREAS





Min stability angle: 0°
Max stability angle: 45°

[mm]



STABILIZATION ADJUSTMENT



[mm]

OVERALL INFORMATIONS

CRANE INFO			DESCRIPTION	U.M	VALUE
		OVERALL DIMENSIONS	Height	mm	2.830
			Length		5.830
			Width		1.840
		BOOM	Length	m	16,3
			Speed	s	50*
		SLEWING	Angle	°	360°
			Speed	rpm	0,67
		LIFTING	Working Angle	°	0°/80°
			Speed	s	Primary: 37 Secondary: 47
		Max Capacity		kg	15.500
		Max Outrigger Bearing Load		kg	11.250 [†]
		Track load		kg/cm ²	0,85
		Travel Speed	Slow	km/h	1
			Fast		2,3
		Gradeability		°	20° (36%) [‡]
		Working Temperature		°C	-10°/+40°

*: Timing without load, fully stabilized and without XP

[†]: Static lifting

[‡]: Engine work limit



OVERALL INFORMATIONS

WEIGHT		CRANE	JF545.2 (with activation)	kg	13.730* †
			Counterweight		3.500

HOOKBLOCKS		HOOK BLOCK	Single Fall	kg	47
			Double Fall		58
			Single Fall Jib		74

ACCESSORIES		JIB	JIBL426	With activation	kg	1.260
				Without activation		1.140
		MANUAL EXTENSIONS	ME1-545.6		kg	95
			ME2-545.6			70
			ME3-545.6			45
			MEH-545.6			90
			MEH-JIB3000.6HA			23
			ME1-JIB3000.6HA			36
		LOW MARKING PADS	WTP-JFM (x92)		kg	300
		OUTRIGGERS MATS	OM500 (x4)		kg	92
		POWERPACK	3-Phase Power pack		kg	80
		PLE	MWP-2PG.JIB3000.6HA		kg	150
			MWP-2PGR.JIB3000.6HA			207

*: Dry weight

†: Estimated fluids weight = 150 kg

OVERALL INFORMATIONS

ENGINE		DIESEL ENGINE	Power	kW	55,4
				HP	74
			Tank capacity	L	75
		ELECTRIC	Voltage	V	400
			Power	kW	13

HYDRAULIC SYSTEM		Maximum Working Pressure		bar	345
		Tank Capacity		L	200
		OIL	Type	Mineral	ISO 6743-4:HV
			Viscosity Grade	VG	46
		DIESEL MAIN PUMP	Type	Variable Flow Pump LS	
			Displacement	cm³/rev	80
			Max Oil Flow	L/min	160
		ELECTRIC MAIN PUMP	Type	Variable Flow Pump LS	
			Displacement	cm³/rev	45
			Max Oil Flow	L/min	60

WINCH PERFORMANCE

W2000-JFM

WINCH	Layer		Max pull line	Standard rope speed
			daN	m/min
	1		2.000*	45
ROPE	4		-*	57,5
	Wire rope	Max load	Ø	Total length
		daN	mm	m
	19x7 avvolgimento destro. Anti-Rotazione	12.750	12	60

HOOK BLOCK	Block type	Load	N° of	
		kg	Sheaves	Lines
	Single fall block	2.000	-	1
	Double fall block	3.500	1	2
	Triple fall block	6.000	1	3

W3000-JFM


WINCH	Layer		Max pull line	Standard rope speed
			daN	m/min
	1		3.000†	28
ROPE	3		-†	36
	Wire rope	Max load	Ø	Total length
		daN	mm	m
	19x7 avvolgimento destro. Anti-Rotazione	18.600	14	60

HOOK BLOCK	Block type	Load	N° of	
		kg	Sheaves	Lines
	Single fall block	3.000	-	1
	Double fall block	6.000	1	2

*: LMI limited at 2.000 kg



†: LMI limited at 3.000 kg

CRANE PERFORMANCE





K	d min	d max
K1	1,6 m	2,0 m
K2	2,0 m	2,6 m
K3	2,6 m	3,1 m
K4	3,1 m	3,2 m
K5	3,2 m	-




JF545.2 - MAIN BOOM



JF545.2 - JIB3000.6HA




JF545.2 - MAIN BOOM




[m] [kg]


JF545.2 - MAIN BOOM




80%
276 bar




60%
207 bar



40%
138 bar





20%
69 bar





[m] [kg]

JF545.2 - MAIN BOOM




JF545.2 - JIB3000.6HA



The load chart refers to the crane in deflection condition.

[m] [kg]

JF545.2 - JIB3000.6HA





[m] [kg]

The load chart refers to the crane in deflection condition.

JF545.2 - JIB3000.6HA




V30



The load chart refers to the crane in deflection condition.

[m] [kg]

JF545.2 - MWP-2PG.JIB3000.6HA




A	PLE	MWP-2PG.JIB3000.6HA	without activation	P_{max}	200 kg
		MWP-2PG.JIB3000.6HA	with activation	P_{max}	200 kg

*: The load chart refers to the crane in deflection condition.

** : The crane is equipped with LMI. The maximum reachable distance may vary by about 1m.

***: The maximum reachable distance can be reached by extending the JIB first and then extending the boom.

JF545.2 - MWP-2PGR.JIB3000.6HA



A	PLE	MWP-2PGR.JIB3000.6HA	without activation	P_{max}	200 kg
		MWP-2PGR.JIB3000.6HA	with activation	P_{max}	200 kg


*: The load chart refers to the crane in deflection condition.
**: The crane is equipped with LMI. The maximum reachable distance may vary by about 1m.
***: The maximum reachable distance can be reached by extending the JIB first and then extending the boom.



Jekko s.r.l


Price List 2023.10 - JF Series

JFS45



ACCESSORIES JF545.2 CDH


CRANE OPTIONS




JIB & ATTACHMENTS



MAN-BASKET



CRAWLER OPTIONS



COLOR & STICKERS PERSONALIZATION



WARRANTY EXTENSION










© All rights reserved


ACCESSORIES FEATURES

MEH-JF545.6


MEH-JIB3000.6HA




ACCESSORIES FEATURES WTP-JFM




MWP-2PG.JIB3000.6HA



MWP-2PGR.JIB3000.6HA



ACCESSORIES FEATURES JIB3000.6HA



SYMBOLS

	Weight		Diesel Engine		Boom Angle		Outriggers mats
	Crane		Power Pack		Boom Length		Hydraulic oil
	Gradeability		Slewing		Jib		Outrigger Load
	Travel Speed		Electric Engine		Hookblock		Working Temperature
	Track Load		Maximum Capacity		Low marking pads		Main Winch
	Person Lifting Equipment		Hook				

- Load limited by LMI
- Load to be limited by the operator
- Load to be verified and limited by the operator
- * Max. moment

REMARKS REFERRING TO LOAD CHART

- HC1 HD5 S2 lifting class in hook configuration, whereas HC1 HD4 S2 lifting class in winch configuration, according to **EN12999:2020** standards.
- Lifting capacities are given in kg.
- Hookblocks, hooks and eventual manual extensions weight is part of the load and therefore must be deducted from lifting capacities.
- Working radius is measured from the column slewing axis.
- Subject to modification of lifting capacities.

29.08.2024 | Rev0.0

SERIAL NUMBER:



Jekko s.r.l.

Via Campardone, 1 - 31014 Colle Umberto (TV) - Italy
info@jekko.it - www.jekko-cranes.com